

SN-IPD57/50AGDR


5MP Fisheye Camera



Key features

- 1/2.5" Progressive Scan CMOS
- 5MP Resolution
- Low bitrate ,Excellent low light performance
- 3D DNR,WDR,ICR,HLC
- Smart IR Up to 10m

Dimension



Accessories

Specifications

CAMERA	
Image Sensor	1/2.5" Progressive Scan CMOS
Min. illumination	Color :0.1Lux@(F1.2,AGC ON);B/W: 0 Lux@(IR LED ON)
Day & Night	ICR (IR Filter Auto)
Shutter Speed	1/5s-1/20000s
Auto Iris	Fixed
Wide Dynamic Range	True WDR
Digital Noise Reduction	2D/3D
Lens	1.5mm
FOV	360 degrees
IR LED	3pcs
IR Range	Up to 10m
IMAGE	
Video Compression	H.265/H.264/MJPEG
Bit Rate (CBR/VBR)	Main stream:500Kbps-12Mbps ;Sub stream 100Kbps-6Mbps
Audio Compression	G.711_A G711_U,RAW_PCM,NONE
Max. Resolution	2560×1920@25fps
Stream	Stream1 2560×1920, 2048×1536, 1280×960@25fps Stream 2 D1/VGA/QVGA@25fps;
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC	Yes
9:16 Corridor Mode	N/A
DIS	Support
ROI	Support
Defog	Support
NETWORK	
Network Protocols:	IPv4,IPv6,IEEE802.1x,HTTP,HTTPS,TCP/IP,UDP/IP,RTSP,DHCP,NTP,SNMP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP ,IGMP, Unicast and Multicast
Alarm Trigger	Motion detection, Network disconnect, Disk alarm ,I/O alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian (Sunell Brand)
System Compatibility	Onvif,CGI,SDK
INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Microphone	Yes (Built-in)
Audio I/O	1ch Audio In,1ch Audio Out
Alarm I/O	N/A
RS485	N/A
BNC Output	N/A
Reset Button	Yes
Edge Storage	Micro SD/SDHC/SDXC slot ,Max 128GB
GENERAL	
Power Supply	DC12V/POE IEEE802.3af
Power Consumption	5W IR LED OFF;8W IR LED ON
Operating Temperature	Starting Temperature:-10°C ~ 50°C (14°F ~ 122°F) Working Temperature:-20°C ~ 50°C (-4°F ~ 122°F)
Operating Humidity	0% - 90% RH
Ingress Protection	N/A
Approvals	CE / FCC / ISO9001 / ISO14001
Product Dimensions	φ 125 × 44.8mm
Product Weight	424g